

• Admin Info:

- lab 6 due today
- lab 7 due next Mon (Nov 4)
- final project proposal due next Fri (Nov 8)

↳ Nov 8 - Dec 9 = work on project

↳ Dec 9 & 11 = in class presentations

↳ Dec 20 = github repos must be finalized

- find a dataset, run an alg on the dataset, do a comparison, evaluate results

8 min per pair & 4 min for questions & feedback

Project Code, Lab Notebook (README.md), presentation slides

running doc [who was working, data, how long, what accomplished]

email:


- title & names
- dataset (n & p)
- algorithm you will develop
- scientific? you're answering?
- way to evaluate results
- interpret, & validate results
- references

• SGD:

Hypothesis Function (Prediction):

- maps input value ($z = w \cdot x$) to probability b/w 0 & 1

$$h_w(x) = p(y = 1 | x) = \frac{1}{1 + e^{-w \cdot x}}$$



Cost Function (want to minimize):

$$J(w) = - \sum_{i=1}^n y_i \log h_w(x_i) + (1 - y_i) \log (1 - h_w(x_i))$$

Gradient of cost w/ respect to a single data point x_i :

$$\nabla J_{x_i}(w) = (h_w(x_i) - y_i) x_i$$

~~the optimal weights~~
~~by updating weights~~
- how much the cost will Δw / a specific weight

• if $w \cdot x < 0 \rightarrow \text{prediction } (h) < 0.5 \rightarrow \text{predict } y = 0$

• if $w \cdot x \geq 0 \rightarrow h \geq 0.5 \rightarrow \text{predict } y = 1$

• SGD for Logistic Regression (binary classification):

set $\vec{w} = \vec{0}$

while cost $J(\vec{w})$ is still changing:

shuffle data points

for $i = 1, \dots, n$:

$$\vec{w} \leftarrow \vec{w} - \alpha \nabla J_{x_i}(\vec{w})$$

store $J(\vec{w})$

derivative of $J(\vec{w})$ wrt x_i

updates the weights based on the gradient of the cost func J wrt x_i

- visualizations are important and want to prevent being:
 - ugly = figure has aesthetic problems but otherwise clear & informative
 - bad = problems related to perception (unclear, confusing, deceiving)
 - wrong = incorrect, mathematical problems

• data types:

- continuous vs. discrete
- can have ordered & unordered qualitative / categorical data

• aesthetics in data visualization:

- based on data types can Δ position, shape, size, color, line width, & line type

- continuous: best option is position on a common scale $\therefore$ but can also use a color or area spectrum

- discrete: could group different shapes or colors

$\hookrightarrow$ can use multiple techniques at the same time - Ex: graph may use same scale for lines and color

• colors can be helpful to visualize data:

- qualitative: use color to distinguish groups, don't want color to show an order between groups

- sequential: use color gradient to show ordering of data

- divergence: use sequential scales based on middle point

$\hookrightarrow$ ~~blue color~~ ~~gradient~~

yellow gradient $\leftarrow$ normally neutral color (white/grey) $\rightarrow$ blue gradient

• be aware of color-blind friendly colors

- also helpful when print in black & white

• overplotting = plotting points on top of each other

- can use just the outline

- jitter = separate points

- can use transparency to see where points overlap

• don't want to use excess ink - Ex: background color might not be helpful

- want to showcase data w/ least amount ^{really} so simple & legible

- can use legend or directly label lines on a graph

- double encoding = coding the same thing twice (Ex: color & scale to show profit) - can be distracting

- can sometimes be helpful - Ex: color a group the same & use shapes to outline

error bar = best practice to say when error is denoting