

CS 369: Introduction to Robotics

Prof. Thao Nguyen
Spring 2026



Haverford
COLLEGE

Outline for today

- Configuration space
- Motion planning
- World representation
- Wavefront planner

Outline for today

- Configuration space
- Motion planning
- World representation
- Wavefront planner

The World consists of...


Obstacles

- Already occupied spaces of the world
- In other words, robots can't go there

Free Space


- Unoccupied space within the world
- Robots “might” be able to go here
- To determine where a robot can go, we need to discuss what a *Configuration Space* is

Example of a world (and robot)



Configuration space

accommodate robot size



Configuration space

What it is




- A set of “reachable” areas constructed from knowledge of both the robot and the world

How to create it


- First abstract the robot as a point object. Then, enlarge the obstacles to account for the robot’s footprint and degrees of freedom
- In our example, the robot was circular, so we simply enlarged our obstacles by the robot’s radius (*note the curved vertices*)

Practice

workspace



Practice



Outline for today

- Configuration space
- Motion planning
- World representation
- Wavefront planner

Motion planning

- Process of finding a feasible path from the start to goal configuration
- If \mathbf{C}_{free} denotes the robot's configuration space,
then a path $\mathbf{p} = (\mathbf{c}_0, \dots, \mathbf{c}_n)$ where $\mathbf{c} \in \mathbf{C}_{\text{free}}$, \mathbf{c}_0 is $\mathbf{q}_{\text{start}}$ and \mathbf{c}_n is \mathbf{q}_{goal}

Evaluation

- Path feasibility
- Distance from obstacles
- Path length
- Planning time

Distance metrics


$$d : \mathbb{R}^2 \times \mathbb{R}^2 \rightarrow \mathbb{R}$$

L1 Metric $d(a,b) = |a_x - b_x| + |a_y - b_y|$

L2 Metric $d(a,b) = \sqrt{(a_x - b_x)^2 + (a_y - b_y)^2}$

Path length

Which is shortest?




depends on the metric

Outline for today

- Configuration space
- Motion planning
- **World representation**
- Wavefront planner


World representation

- Can always use a continuous representation
- For simplicity, use uniform-sized grid cells




Grid representation

- Distance is reduced to discrete steps
 - what does it mean for the robot to be inside a grid?
- Direction is now limited from one adjacent cell to another




Connectivity

- 8-Point Connectivity
- 4-Point Connectivity
 - (approximation of the L1 metric)



Occupancy grid

- A grid where each cell encodes occupancy information
 - Binary: a cell is either occupied (1) or free (0)
 - Probabilistic
- How to determine occupancy?
 - Optimistic
 - Pessimistic



Outline for today

- Configuration space
- Motion planning
- World representation
- Wavefront planner

Wavefront planner

- Common algorithm used to determine the shortest path between two points
- Setup:
 - Label free space with 0
 - Label obstacles with 1
 - Label start as START
 - Label the goal as 2

7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
3	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Wavefront planner

Starting with the goal, set all adjacent cells with "0" to the current cell value + 1

- this example uses 8-point connectivity

7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
3	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
1	0	0	0	0	0	0	0	0	0	0	0	0	0	3	3	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	2	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Wavefront planner

Repeat with the modified cells

7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
3	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
2	0	0	0	0	0	0	0	0	0	0	0	0	4	4	4	
1	0	0	0	0	0	0	0	0	0	0	0	0	4	3	3	
0	0	0	0	0	0	0	0	0	0	0	0	0	4	3	2	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Wavefront planner

Repeat again

7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	
3	0	0	0	0	1	1	1	1	1	1	1	1	5	5	5	
2	0	0	0	0	0	0	0	0	0	0	0	0	5	4	4	
1	0	0	0	0	0	0	0	0	0	0	0	0	5	4	3	
0	0	0	0	0	0	0	0	0	0	0	0	0	5	4	3	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

And again

7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
4	0	0	0	0	1	1	1	1	1	1	1	1	6	6	6	
3	0	0	0	0	1	1	1	1	1	1	1	1	5	5	5	
2	0	0	0	0	0	0	0	0	0	0	0	0	6	5	4	
1	0	0	0	0	0	0	0	0	0	0	0	0	6	5	4	
0	0	0	0	0	0	0	0	0	0	0	0	0	6	5	4	
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Wavefront planner

Repeat until no 0's are adjacent to cells with values ≥ 2

- 0's will only remain if unreachable regions exist

7	18	17	16	15	14	13	12	11	10	9	9	9	9	9	9	9
6	17	17	16	15	14	13	12	11	10	9	8	8	8	8	8	8
5	17	16	16	15	14	13	12	11	10	9	8	7	7	7	7	7
4	17	16	15	15	1	1	1	1	1	1	1	1	6	6	6	6
3	17	16	15	14	1	1	1	1	1	1	1	1	5	5	5	5
2	17	16	15	14	13	12	11	10	9	8	7	6	5	4	4	4
1	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	3
0	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2
	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Wavefront planner

To find the shortest path, simply always move toward a cell with a lower number (except value 1)

- The numbers generated by the Wavefront planner are roughly proportional to their distance from the goal

Two possible shortest paths shown

